، تخصصی آزمون کارشناسی ارشد





محل امضا:

نام خانوادگی:

صبح پنجشنبه 901.7/18



امام خمینی (ره)

وزارت علوم. تحقیقات و فنّاوری سازمان سنجش آموزش كشور

آزمون ورودي دورههاي كارشناسيارشد ناپيوستهٔ داخل ـ سال 1395

مجموعة مهندسي برق ـ كد 1251

مدت پاسخگویی: ۱۰۵ دقیقه

تعداد سؤال: ۵۴

عنوان مواد امتحاني، تعداد و شمارهٔ سؤالات

رديف	مواد امتحانی	تعداد سؤال	از شماره	تا شماره
١	زبان عمومی و تخصصی(انگلیسی)	r. 1 r.		۲٠
۲	ریاضیات (معادلات دیفرانسیل، ریاضیات مهندسی، آمار و احتمالات)	۱۲	r)	FY
٣	مدارهای الکتریکی ۱ و ۲	١٢	۴٣	۵۴

این آزمون نمرهٔ منفی دارد. استفاده از ماشین حساب مجاز نی

ی چاپ، تکثیر و انتشار سوالات به هر روش (الکترونیکی و ...) پس از برگزاری آزمون، برای تمامی اشخاص حقیقی و حقوقی تنها با مجوز این سازمان مجاز میباشد و با متخلفین برابر مقررات رفتار می شود

مجموعة مهندسي برق صفحه ۲ صفحه ۲

ربان عمومی و تخصصی(انگلیسی):

l-:	In spite of the considerable effort, many questions still remain unanswered, th justifying continuous research in this field of inquiry.							
	1) taken	2) wasted	3) invested					
2-	The fact that "innovation" is frequently alluded to not only the importance of t topic but also generates much confusion, because its meaning depends strongly on t							
	context in which i		,	and artema arrange, and				
	1) highlights	2) circumvents	3) alleges	4) cites				
3-		He was stopped by the police for transgressing the law; he had actually been driving fas						
	than the speed							
		2) permit						
1-	I thought he was	really hurt and beca	ame worried but late	er I realized that he was ju				
	1) emerging	faking	revealing	4) deserving				
5-	Irene's argument could resist them.		's innocence were so	that no jury memb				
		2) enthusiastic						
5-	Believe it or not, laughing is considered to be one of the easiest exercises that cure many diseases.							
	 transparent 		provocative					
7-	While Alex is very spendthrift and spends money recklessly, his brother Stew is question and spends only when it is necessary.							
		assiduous						
3-	they needed at ho	me in virtual wards?		they could access all the ca				
200		2) necessitate						
9-	The underlying message of the film is that love can transcend all 1) impacts 2) barriers 3) analogies 4) interjections							
10-	It is no use arguing over such a trifling matter; instead we should discuss the matters importance and 1) pragmatism 2) facility 3) priority 4) jeopardy							
	 pragmatism 	2) facility	3) priority	4) jeopardy				

Genetically modified superhumans. Babies born with made-to-order characteristics. The idea has been explored in everything from academic journals (11) ----- movies. CRISPR technology could make it (12) -----

The ability to alter human genes in a way that can be passed onto offspring, (13) ----- germline engineering, has long been possible. But (14) ------ genetically modify animals were so inefficient and crude (15) ----- no sane biologist

تست؛ وبسایت تخصصی آزمون کارشناسی ارشد

112A مجموعة مهندسي برق صفحه ۳

would dream of using them on humans. Tinkering with the genes inside people has been limited to gene therapy, where the changes don't get passed to the next generation.

1) in 112) through

3) for

4) to

12-1) to be real 2) as real

3) a reality

4) being a reality

1) called 132) to be called

3) which called

4) is called

1) as

15-

1) until recently the methods available to 14-

2) the until recently methods available to

3) the methods available to until recently

4) until available to recently methods

2) that

3) because

4) such that

PART C: Reading Comprehension:

Directions: Read the following three passages and answer the questions by choosing the best choice (1), (2), (3), or (4). Then mark the correct choice on your answer sheet.

PASSAGE 1:

Though relatively new in the world of wireless communications, the history of millimeter wave technology goes back to the 1890's when Bose was experimenting with millimeter wave signals at just about the time when his contemporaries like Marconi were inventing radio communications. Following Bose's research, millimeter wave technology remained within the confines of university and government laboratories for almost half a century.

The propagation characteristics of millimeter waves through the atmosphere depend primarily on atmospheric oxygen, humidity, fog and rain. The signal loss due to atmospheric oxygen, although a source of significant limitation in the 60 GHz band, is almost negligible in the 70 and 80 GHz bands. The effect of water vapor, which varies depending on the absolute humidity, is between zero and about 3dB loss per km at very high humidity and temperature.

The performance reliability of a communication system is often benchmarked in terms of availability percentage of the system. It signifies the average percentage of the time the system is expected to operate to its specification. As stated before, there are other factors that dictate the performance of a millimeter wave link. An intense rain event may cause significant attenuation of millimeter wave signals, but it may not cause an outage of a millimeter wave data link if the link has sufficient margin.

One of the key advantages of millimeter wave communication technology is the large amount of spectral bandwidth available. The bandwidth available in the 70 GHz and 80 GHz bands, a total of 10 GHz, is more than the sum total of all other licensed spectrum available for wireless communication. With such wide bandwidth available, millimeter wave wireless links can achieve capacities as high as 10 Gbps full duplex, which is unlikely to be matched by any lower frequency RF wireless technologies.

مجموعة مهندسي برق ماك صفحه ۴ صفحه ۴

16- Based on the text, which statement is true?

- 1) Universities and government laboratories banned the use of millimeter waves.
- 2) The millimeter waves were used by Marconi for radio communications.
- 3) The millimeter waves were rapidly used right after Bose's experiment.
- The results of Bose's experiment were not received the attention it deserved by industry.

17- According to text, we can conclude that ------

- The environmental factors have a significant role in the propagation characteristics of millimeter waves.
- The atmospheric oxygen is more destructive when the frequency of millimeter waves increases.
- The total attenuation due to humidity does not depend on the transmitter receiver distance.
- 4) Millimeter waves are less attenuated when it is very humid.

18- What is the main adverse attribute of the transmission using millimeter waves?

- 1) It can be used for high rate transmission.
- It is highly sensitive to severe weather conditions.
- 3) It is a solution for spectrum scarcity.
- 4) The large amount of the available bandwidth.

19- The word "relatively" in the first paragraph, can be replaced by ------

- 1) absolutely 2) entirely 3)
 - 3) comparatively 4) utterly

4) attained

- 20- The word "benchmarked" in the third paragraph can be replaced by ------
 - 1) visualized 2) evaluated 3) completed

PASSAGE 2:

In the 20th century, the world's power systems were based on alternating current (AC). The key to AC's triumph was that power could be transformed to higher voltages by use of magnetic induction and then sent over long distances at low currents, minimizing the losses due to resistance; at the destination, the system would reduce the voltage for local distribution. At the time, there was no way to do the same with direct current (DC). However, power engineers also knew that a DC system operating at high voltage would be superior to AC for the same task, since the amount of electricity lost during DC transmission would be far less.

Let's say you are transmitting a given amount of power by high-voltage DC (HVDC): When you double the voltage, you need only half the current of a comparable AC system, thus reducing the line losses by a factor of four. You also need a lot less wire, as DC current penetrates the entire conductor of a power line, whereas AC current remains largely near the surface. In other words, for the same conductor size, the effective resistance is greater with AC, and more power is lost as heat. In practice, that means the overall transmission infrastructure for AC far exceeds that for DC.

HVDC also allows for the easy transfer of power between grids that are operating at different frequencies. The converters, cables, breakers, and other components for HVDC are more expensive than those for AC, so it only makes economic sense to use HVDC over distances of 500 km or more. But that break-even distance has continued to come down as the cost of DC components drops. With these advantages in mind, power engineers experimented with DC transmission technology throughout the 20th century.

مجموعة مهندسي برق مفحه ۵ معموعة مهندسي برق

The key building block for HVDC was and still is the converter, located at either end of an HVDC line. It serves to convert high-voltage AC to high-voltage DC and DC back to AC. Through the 1960s, such converters relied on mercury arc valves, which were basically electronic switches that could only be turned on and not off, thereby limiting their functionality and resulting in substantial losses.

21- How is passage organized?

- 1) The merits and drawbacks of AC and DC in power distribution systems are compared.
- 2) The history of the power systems in the 21st century is reviewed.
- It explains the break even distance.
- 4) The characteristics of the HVDC are outlined.

22- Why in the 20th century, power engineers did not use DC systems for power transmission?

- Low demand for lossless distribution lines.
- 2) Short distance transmission lines.
- 3) Lack of knowledge about its advantages.
- 4) Inefficiency of DC components.

23- According to the text, HVDC has the following advantages over HVAC except ------

- 1) cheaper transmission infrastructure.
- 2) easier power grids connection.
- 3) use of magnetic induction.
- 4) lower transmission loss.

24- What are the main components in HVDC?

1) transmission lines.

2) AC/DC converters.

3) circuit breakers.

4) transformers.

25- Which of the following is the most likely topic of the paragraph following the passage?

- 1) technology of mercury-arc valves in 1960s.
- 2) AC's triumph in modern power transmission systems.
- history of power systems in the 21st century.
- 4) advancements in AC/DC converters.

PASSAGE 3:

Effective network planning is essential to cope with the increasing number of mobile broadband data subscribers and bandwidth-intensive services competing for limited radio resources in cellular systems. Operators have met this challenge by increasing capacity with new radio spectrum, adding multi-antenna techniques and implementing more efficient modulation and coding schemes.

However, these measures alone are insufficient in the most crowded environments and at cell edges where performance can significantly degrade. Operators are also adding small cells and tightly-integrating these with their macro networks to spread traffic loads, widely maintain performance and service quality while reusing spectrum most efficiently.

One way to <u>expand</u> an existing macro-network, while maintaining it as a homogeneous network, is to "densify" it by adding more sectors per base station or deploying more macro base stations. However, reducing the site-to-site distance in the macro-network can only be pursued to a certain extent because finding new macro-sites becomes increasingly difficult and can be expensive, especially in city centers. An

مجموعة مهندسي برق معموعة مهندسي برق صفحه ۶

alternative is to introduce small cells through the addition of low-power base stations. The actual cell size depends not only on base station power but also on antenna position, as well as the location environment; e.g. rural or city, indoor or outdoor. Small cells are primarily added to increase capacity in hot spots with high user demand and to fill in areas not covered by the macro network - both outdoors and indoors. They also improve network performance and service quality by offloading from the large macro-cells. The result is a heterogeneous network with large macro-cells in combination with small cells providing increased bitrates per unit area.

26- According to the text, what is the main challenge in the network planning?

- 1) Services which require significant bandwidths.
- 2) Systems with rising number of subscribers.
- 3) Spectrum scarcity.
- 4) All of the above.

27- Based on the text, which statement is valid?

- The problem of network planning has been solved by increasing the number of sectors per base station.
- Utilizing multi-antenna systems is enough for efficient network planning in the crowded area.
- Heterogeneous networks expand the capacity of the cellular systems.
- Improving the modulation and coding is the most productive approach to be used in cell edges.

28- Which of the following approaches does not result in a homogeneous network?

- Deploying small cells with low power base stations in addition to the existing macro base station.
- 2) Implementing more efficient techniques for modulation and coding.
- 3) Densifying the network by implementing more macro base stations.
- 4) Expanding the number of sectors for each base station.

29- According to the text, we can conclude that -----

- Densifying the network with more macro base stations in hot spots is an easy and economically efficient task.
- Small cells in heterogeneous networks cover the areas with low coverage from macro base stations.
- 3) The actual size of a cell is affected only by the power of its base station.
- 4) The number of macro base stations can be increased to any arbitrary level.

30- The word "expand" in the third paragraph, can not be replaced by which of the following words?

- 1) Develop
- 2) Extend
- 3) Enlarge
- 4) Restrict

مفحه ۷ صفحه ۷

مجموعة مهندسي برق

رياضيات (معادلات ديفرانسيل، رياضيات مهندسي، آمار و احتمالات):

به روش تغییر پارامتر باشد، $y(t)=u_1\cos\pi t+u_7\sin\pi t$ به روش تغییر پارامتر باشد، $y''+9y=\sec^{\mathsf{Y}}(\pi t)$

$$c_1 - \frac{1}{\cos rt}$$
 (1

$$c_1 + \frac{1}{\cos rt}$$
 (7

$$c_1 + \frac{r}{\cos rt}$$
 (r

$$c_1 - \frac{\pi}{\cos \pi t}$$
 (F

٣٢- جواب مسئلة مقدار اولية زير، كدام است؟

$$\begin{cases} x \frac{dy}{dx} = y + x \sec(\frac{y}{x}) \\ y(1) = \frac{\pi}{r} \end{cases}$$

$$\cos(\frac{y}{x}) = \operatorname{Ln}|x| - \frac{\sqrt{r}}{r}$$
 (1)

$$\cos(\frac{y}{y}) = \operatorname{Ln} |x| + \frac{\sqrt{y}}{y}$$
 (7)

$$\sin(\frac{y}{x}) = \operatorname{Ln} |x| - \frac{\sqrt{r}}{r} (r^{2})$$

$$\sin(\frac{y}{x}) = \operatorname{Ln}|x| + \frac{\sqrt{y}}{y}$$
 (4

°22 مجموعه نقاط تکین معادلهٔ $\frac{1}{x}$ + $xy' = \frac{1}{x}$ مجموعه نقاط تکین معادلهٔ -۳۳

$$\left\{...,\frac{-r\pi-r}{r},\frac{-\pi-r}{r},\circ,\frac{\pi-r}{r},\frac{r\pi-r}{r},...\right\} \ (1)$$

$$\left\{...,\frac{-r'\pi-r}{r},\frac{-\pi-r}{r},\frac{\pi-r}{r},\frac{r\pi-r}{r},...\right\} (7)$$

$$\left\{...,\frac{-r\pi-r}{r},\frac{-\pi-r}{r},\circ,\frac{\pi-r}{r},\frac{r\pi-r}{r},...\right\} \ (r^{*}$$

$$\left\{...,\frac{-r\pi-r}{r},\frac{-\pi-r}{r},\frac{\pi-r}{r},\frac{r\pi-r}{r},...\right\} \ (f$$

جموعة مهندسي برق مفحه ۸ صفحه ۸

۳۴ اگر جواب معادلهٔ $y = x^Ty'' + xy' + (x^T - 1)y = 0$ را به روش فروبنیوس به ازای ریشهٔ بزرگ تر معادلهٔ مشخصه در نظر بگیریم، روابط بازگشتی بین ضرایب سری به چه صورت است؟

$$a_n = \frac{a_{n-\gamma}}{1-n^{\gamma}}$$
 (1)

$$a_n = \frac{a_{n-1}}{n^{\gamma} - 1} (\gamma$$

$$a_{n+\tau} = \frac{a_n}{(n+\tau)(n+\tau)} \ (\tau$$

$$a_{n+\tau} = \frac{-a_n}{(n+\tau)(n+\tau)} \quad (\tau$$

ست. از ضرب $x^{\tau} = -\tau \sum_{n=1}^{\infty} (\frac{\pi^{\tau}}{n} - \frac{9}{n^{\tau}})(-1)^n \sin(nx)$ و $x = -\tau \sum_{n=1}^{\infty} \frac{(-1)^n}{n} \sin(nx)$ ، $-\pi < x < \pi$ است. از ضرب $-\tau \leq x < \pi$

داخلی این دو تابع، کدام نتیجه، حاصل میشود؟

$$\sum_{n=1}^{\infty} \frac{1}{n^{r}} (\pi^{r} - \frac{9}{n^{r}}) = \frac{\pi^{r}}{10}$$
 (1)

$$\sum_{n=1}^{\infty} \frac{1}{n^{\tau}} (\pi^{\tau} - \frac{\mathfrak{s}}{n^{\tau}}) = \frac{\pi^{\mathfrak{s}}}{\Delta} (\tau$$

$$\sum_{n=1}^{\infty} \frac{1}{n^{\tau}} (\pi^{\tau} - \frac{9}{n^{\tau}}) = \frac{\pi^{\tau}}{\Delta} (\tau^{\tau} - \frac{9}{n^{\tau}})$$

$$\sum_{n} \frac{1}{n^{\tau}} (\pi^{\tau} - \frac{9}{n^{\tau}}) = \frac{\pi^{\tau}}{10^{\circ}} (9)$$

مجموعة مهندسي برق مفحه ٩ صفحه ٩

سری فوریه با f(x,t) در هر لحظه f(x,t) نسبت به متغیر f(x,t) تکهای هموار بوده و قابل نمایش به صورت یک سری فوریه با ضرایب پیوستهٔ $f_n(t)$ نسبت به پایهٔ متعامد مورد نیاز مسئلهٔ مقدار اولیه $f_n(t)$ نسبت به پایهٔ متعامد مورد نیاز مسئلهٔ مقدار اولیه $f_n(t)$

$$\begin{cases} u_{tt} - a^{\Upsilon} u_{xx} = f(x, t), \circ < x < L, t > \circ \\ u(x, \circ) = \circ, u_t(x, \circ) = \circ, \circ \le x \le L \\ u(\circ, t) = \circ = u(L, t), t > \circ \end{cases}$$

اگر G کدام است؟ $u(x,t)=\int_0^t\int_0^LG(x,z,t- au)\,f(z, au)dzd au$ گدام است؟

$$\frac{\tau}{\pi a} \sum_{n=1}^{\infty} \frac{1}{n} \sin \frac{n\pi}{L} a(t-\tau) (\sin \frac{n\pi x}{L}) (\sin \frac{n\pi z}{L})$$
 (1)

$$\frac{\tau}{\pi} \sum_{n=1}^{\infty} \frac{1}{n} \sin \frac{n\pi}{L} a(t-\tau) (\sin \frac{n\pi x}{L}) (\sin \frac{n\pi z}{L})$$
 (Y

$$\frac{\tau}{\pi a} \sum_{n=1}^{\infty} \frac{1}{n} \sin \frac{\tau n \pi}{L} a(t-\tau) (\sin \frac{\tau n \pi x}{L}) (\sin \frac{\tau n \pi z}{L}) (\tau n \pi x) (\tau n \pi x)$$

$$\frac{\tau}{\pi} \sum_{n=1}^{\infty} \frac{1}{n} \sin \frac{\tau n \pi}{L} a(t-\tau) \left(\sin \frac{\tau n \pi x}{L}\right) \left(\sin \frac{\tau n \pi z}{L}\right) (\tau + \tau) \left(\sin \frac{\tau n \pi x}{L}\right)$$

 $\mathbf{u}(\circ,t) = \mathbf{u}(\pi,t) = \circ$ برای حل معادلهٔ ناهمگن حرارت $\mathbf{u}(\mathbf{u},t) = \mathbf{u}_{xx} + \mathbf{h}(\mathbf{x},t)$ برای حل معادلهٔ ناهمگن حرارت $\mathbf{u}(\cdot,t) = \mathbf{u}_{xx} + \mathbf{h}(\mathbf{x},t)$

که در آن تابع $u_n(t)$ تکهای هموار است، اگر $u_n(t)\sin(nx)=\sum_{n=1}^\infty u_n(t)\sin(nx)$ از معادلهٔ که در آن تابع

 $A_n(t)$ ديفرانسيل $u_n'(t) + n^\intercal \pi^\intercal u_n = A_n(t)$ به دست می آید، عبارت $u_n'(t) + n^\intercal \pi^\intercal u_n = A_n(t)$

$$\int_{0}^{\pi} h(x,t) \sin nx \, dx \quad (1)$$

$$\pi \int_{0}^{\pi} h(x,t) \sin nx \, dx$$
 (Y

$$\frac{\pi}{r} \int_{r}^{\pi} h(x,t) \sin nx \, dx$$
 (7)

$$\frac{r}{\pi} \int_{0}^{\pi} h(x,t) \sin nx \, dx$$
 (f

جموعة مهندسي برق مفحه ١٠ صفحه ١٠

در درون مرز |z|=7 کدام است؟ (Log) شاخهٔ اصلی $f(z)=\frac{Log(iz+7)}{(z-1)\cosh(\pi z)\sin z}$ در درون مرز z=7 کدام است؟ z=7 شاخهٔ اصلی

تابع لگاریتم است)

- 0 (1
- T (T
- 9 (
- ۴) ہیشمار

۱۳۹ ماست واصل از z=1+i به z=0 ، در طول خط راست واصل از z=1+i به z=0 ، کدام است z=1+i

- $1+\frac{i}{r}$ (1
- $\frac{1}{r}(i+1)$ (7
- $\frac{1}{r}(i-1)$ (r
 - 1-i

و متغیر متغیر المی المی المی المی المی با استفاده از تغییر متغیر $B(p,q)=\int_{0}^{1}t^{P-1}(1-t)^{q-1}\mathrm{d}t$ اگر -4

- (به ازای a < 1 مقدار (a < 1 هدار (a < 1)، کدام است a < 1 هدار (a < 1)، کدام است
 - $\frac{\pi}{\sinh(\pi a)}$ (1
 - $\frac{\Upsilon\pi}{\sin(\pi a)}$ (Υ
 - $\frac{\pi}{\sin(\pi a)}$ (**
 - $\frac{\pi}{r\sin(\pi a)}$ (f

P(A) = $\frac{1}{\pi}$ و $P(B) = \frac{\gamma}{\pi}$ ، $P(A \mid B) + P(B \mid A) = \frac{\pi}{4}$ مقدار -۴۱ و $P(A \mid B)$ و $P(A \mid B)$ مقدار -۴۱ د برای دو پیشامد $P(A \mid B)$ و $P(A \mid B)$

- P(AUB) كدام است؟
 - 1 (1
 - <u>۵</u> (۲
 - ÷ (4
 - 1 (4

جموعة مهندسي برق مفحه ١١ صفحه ١١

k) و Y به شکل زیر است. میانهٔ متغیر مشترک متغیرهای تصادفی X و Y به شکل زیر است. میانهٔ متغیر تصادفی Y کدام است Y کدام است Y عدد ثابت است)

$$f_{XY}(x,y) = \begin{cases} kx & \circ < x < y < 1 \\ \circ & \text{otherwise} \end{cases}$$

مدارهای الکتریکی ۱ و ۲:

۹- در مدار زیر، بهازای چه مقدار α مقاومت معادل دیده شده از دو سر α و α به مقدار α است


$$\alpha = \frac{1}{r}$$
 (7

$$\alpha = 1 \ \text{(r}$$

$$\alpha \neq 0$$
 تمامی مقادیر (۴


مجموعة مهندسي برق معموعة مهندسي برق معموعة علام 112A

۴۴ در مدار زیر، باتوجه به مشخصهٔ مقاومت غیرخطی $v_N - i_N$ ، جریان i چند آمپر است؟




- $-\frac{r}{\Delta} (1)$ $-\frac{q}{10} (7)$
- $-\frac{\lambda}{L}$ (L
- × (4

در مدار زیر که شامل مقاومت غیرخطی با مشخصهٔ نشانداده شده است، اگر $v(\overline{\circ}) = \Lambda V$ باشد، بعد از چه مدتی -۴۵




- ln 4 (1
- ln 11 (7
 - 1 (1
 - Y (4




مجموعة مهندسي برق معموعة مهندسي برق معموعة مهندسي برق

و مدار زیر با $v_C(\overline{\circ}) = \Upsilon V$ و $v_C(\overline{\circ}) = \Upsilon V$ ، مقدار $i''_L({\circ}^+)$ ، چند آمپر است؟




۴۷ در مدار زیر، مقدار بیشینهٔ توان منبع در حالت دائمی سینوسی، چند وات است؟

-19 (4



ه و a در فرکانس $\alpha = r \frac{rad}{s}$ به مقداری برای خازن a ، امپدانس دیده شده از سرهای a و a در فرکانس a به صورت سلفی



۴۹ در گراف ۶ شاخهای و ۴ گرهی، ماتریس کات ستهای اساسی به صورت زیر است. ماتریس حلقه های اساسی کدام است؟

$$Q = \begin{bmatrix} -1 & 1 & 1 & 1 & 0 & 0 & 0 \\ -1 & 1 & -1 & 0 & 0 & 0 \\ 1 & 0 & 1 & 1 & -1 & 0 \\ -1 & 0 & 0 & 0 & 1 & 1 \end{bmatrix}$$

$$\mathbf{B} = \begin{bmatrix} 1 & 1 & 0 & -1 & 0 & 1 \\ 0 & 1 & 1 & -1 & 0 & 0 \\ 0 & 0 & 0 & 1 & 1 & -1 \end{bmatrix} (1)$$

$$\mathbf{B} = \begin{bmatrix} 1 & -1 & \circ & 1 & \circ & -1 \\ \circ & -1 & 1 & 1 & \circ & \circ \\ \circ & \circ & \circ & -1 & 1 & 1 \end{bmatrix} (7)$$

$$B = \begin{bmatrix} 1 & 0 & 0 & 1 & -1 & 1 \\ 0 & 1 & 0 & 1 & -1 & 0 \\ 0 & 0 & 1 & 0 & 1 & -1 \end{bmatrix}$$
 (T

$$B = \begin{bmatrix} 1 & \circ & \circ & -1 & 1 & -1 \\ \circ & 1 & \circ & -1 & 1 & \circ \\ \circ & \circ & 1 & \circ & -1 & 1 \end{bmatrix} (f$$

میاشد، ماتریس \mathbf{A} در معادلات حالت مدار $\mathbf{x}=\begin{bmatrix} \mathbf{i}(t) \\ \mathbf{v}_1(t) \end{bmatrix}$ میاشد، ماتریس \mathbf{A} در معادلات حالت مدار $-\Delta \mathbf{v}$

است؟ $\dot{\mathbf{x}} = \mathbf{A}\mathbf{x} + \mathbf{B}\mathbf{v}$

$$v_s \stackrel{i}{\bigoplus} v_{\gamma} \stackrel{i}{\bigoplus} v_{\gamma} \stackrel{V_{\gamma}}{\bigoplus} v_{\gamma} \stackrel{V_{\gamma}}{\bigoplus} v_{\gamma} \stackrel{V_{\gamma}}{\bigoplus} v_{\gamma}$$

$$\begin{bmatrix} \circ & -\frac{1}{r} \\ 1 & -\frac{\Delta}{r} \end{bmatrix} (1)$$

$$\begin{bmatrix} \circ & -\frac{1}{r} \\ -1 & \frac{r}{r} \end{bmatrix} (7)$$


$$\begin{bmatrix} \circ & -\frac{r}{t} \\ 1 & -\frac{r}{t} \end{bmatrix} \alpha r$$

$$\begin{bmatrix} \circ & -\frac{r}{r} \\ 1 & -\frac{\delta}{r} \end{bmatrix} (r$$


مجموعة مهندسي برق مفحه ١١٤٨ صفحه ١١


 ۵۱ در مدار زیر، بهازای کدام مقدار n، ضریب جملهٔ بیش ترین درجهٔ معادلهٔ مشخصهٔ مدار، صفر می شود؟ (معادلهٔ مشخصهٔ مدار، معادلهٔ تمام فرکانس های طبیعی مدار است.)

- n = 1 (1
- n > r (r
- n (۳ هر مقداری می تواند باشد.
 - ۴) جوابی وجود ندارد.




 $v_{AB} = \frac{1}{90} E$ (۲) و در شکل (۱) و $v_{AC} = \frac{1}{9} E$ (۱) و در شکل (۱) و تابت است. اگر در شکل (۲) و در شکل (۲) و در شکل (۲) باشد، مقدار $v_{AB} = \frac{1}{90} E$ (۲) و در شکل (۲) و






- ٨٠٠ (١
- 900 (7
- 1100 (
- 1900 (F

۵۳ در شکل زیر، اگر دترمینان ماتریس ادمیتانس دوقطبی نشانداده شده در $\frac{1}{v}$ = s، برابر با ۱۲ باشد، مقاومت R چند



مجموعة مهندسي برق ماعد ما 112A صفحه ۱۶

در مدار زیر با $i_{\rm S}={
m u}(t)$ ، پاسخ حالت صفر $v_{
m o}$ کدام است؟ ($s_{
m v}$ و $s_{
m v}$ فرکانسهای طبیعی مدار میباشند) - Δt



$$v_o(t) = \frac{1}{r}u(t) + tu(t) + k_1e^{s_1t} + k_re^{s_rt}$$
 (1)

$$v_{_{\mathrm{o}}}(t) = \frac{1}{r}\delta(t) + \frac{1}{r}tu(t) + k_{1}e^{S_{1}t} + k_{r}e^{S_{r}t} \ (\Upsilon$$

$$v_o(t) = \frac{1}{r}u(t) + \frac{1}{r}tu(t) + k_1e^{s_1t} + k_re^{s_rt}$$
 (T

$$v_{o}(t) = \frac{1}{r}\delta(t) + \frac{1}{r}u(t) + \frac{1}{r}tu(t) + k_{1}e^{s_{1}t} + k_{r}e^{s_{r}t}$$
 (4)